

Combi-Grip®

Ceramic Lagging Tiles

Combi-Grip® tiles are embedded in our Richwood R2000LS premium rubber compound. This combination ensures the ceramic tiles will stand up to your toughest conveyor applications.

Combi-Grip® is custom-made to provide maximum ceramic coverage on the width of your pulley. The easy-to-install strips are pre-buffed, primed and packaged in a durable plastic sleeve to ensure a clean, ready-to-install bond surface.



Combi-Grip® ND



Combi-Grip® Profile

We offer hands-on installation training. All Richwood products are made in USA and backed by our 3-year Manufacturer's Warranty.

(304) 525-5436 | (800) 237-6951

richwood.com

Combi-Grip®


Thickness	Width	Max Length	Max PIW	Weight/Lineal Ft.	Ceramic Type	Available Compound
5/8"	19"	120"	<475	4.95#	Dimpled	SBR, MSHA

Overall Tile Size	0.30" x 1" x 1"
Total Ceramic Surface Area	17.00%
Raised Dimples Per Linear Foot	520
Dimple Size	Oval (0.0197" sq)
Friction Value	.4 to .6 Depending on Application
Factory Prepared Bonding Surface	yes

	R2000LS SBR	MSHA Grade (#IC-182/4)
Durometer	60+/-5 Shore A	60+/-5 Shore A
Elongation	525%	500%
Tensile Strength	3800	2000

Combi-Grip® ND

Thickness	Width	Max Length	Max PIW	Weight/Lineal Ft.	Ceramic Type	Available Compound
5/8"	19"	120"	1500	4.95#	Smooth	SBR, MSHA
3/4"	19"	120"	>1500	6.24#	Smooth	SBR, MSHA



 **RICHWOOD**
Proven Solutions. Expert Advice.